

sinopé



Smart Thermostat for Electric Heating TH1123ZB-C4



Electric baseboard



Fan-forced convector (long cycle)



Convector (short cycle)



Radiant ceiling heating

CONNECTS WITH
Control4[®]
CERTIFIED

■ FEATURES*

- Backlit display
- Detects the connected load
- Lockable buttons
- Personalization of the minimum and maximum temperatures available for thermostat control
- Indoor and outdoor temperatures featured on the thermostat display
- Temperature displayed in °C or °F

* Some features must be programmed by a Control4 integrator.

■ COMMUNICATION

Protocol: Zigbee 3.0
Frequency: 2.4 GHz
Transmission power: +20 dBm
Receiver sensitivity: -108 dBm
Encryption key: AES-128



Also available:
Smart Thermostat for
Electric Heating (4000 W)
TH1124ZB-C4

- Remote control with your smartphone, tablet or computer*
- Schedule programming
- Voice control with Amazon Alexa and Google Assistant

* Remote access requires a permanent Internet connection and a Control4 controller.

■ TECHNICAL SPECIFICATIONS

Operating voltage: 120/208/240 Vac, 60 Hz
Bilateral triode switch (triac)

Maximum load (resistive load only):

TH1123ZB

Min. 1.25 A / 300 W @ 240 Vac
Max. 12.5 A / 3000 W @ 240 Vac

TH1124ZB

Min. 1.25 A / 300 W @ 240 Vac
Max. 16.7 A / 4000 W @ 240 Vac

Setpoint range: 5 °C to 30 °C (41 °F to 86 °F)
Display range: 0 °C to 50 °C (32 °F to 99 °F)
Storage: -20 °C to 50 °C (-4 °F to 122 °F)
Operation: 0 °C to 50 °C (32 °F to 122 °F)
Resolution: ± 0.5 °C (± 1 °F)
3-year warranty

■ CERTIFICATION



■ STANDARDS

Conforms to CSA-C828-19

