

sinopé



## Non-Programmable Double-Pole Thermostat TH1500NP



Electric baseboard



Fan-forced convector



Convector



Radiant ceiling heating

## ■ FEATURES\*

- Accuracy of  $\pm 1^\circ\text{F}$  [ $\pm 0.5^\circ\text{C}$ ] for maximum savings and comfort
- Detects the connected load
- Elegant backlit display
- Personalization of the minimum and maximum temperatures available for thermostat control
- Simple installation (4 wires)
- Temperature displayed in  $^\circ\text{C}$  or  $^\circ\text{F}$

Mounting screws and wire connectors included

## ■ CERTIFICATION



## ■ STANDARDS

Conforms to CSA-C828-19

## ■ TECHNICAL SPECIFICATIONS

**Operating voltage:** 120/208/240/277 Vac, 50/60 Hz  
**Relay switching**

**Maximum load:**

1800 W @ 120 Vac / 15 A  
3120 W @ 208 Vac / 15 A  
3600 W @ 240 Vac / 15 A  
4155 W @ 277 Vac / 15 A

**Setpoint range:** 41  $^\circ\text{F}$  to 97  $^\circ\text{F}$  [5  $^\circ\text{C}$  to 36  $^\circ\text{C}$  ]

**Display range:** 32  $^\circ\text{F}$  to 99  $^\circ\text{F}$  [0  $^\circ\text{C}$  to 50  $^\circ\text{C}$ ]

**Storage:** -4  $^\circ\text{F}$  to 122  $^\circ\text{F}$  [-20  $^\circ\text{C}$  to 50  $^\circ\text{C}$ ]

**Resolution:**  $\pm 0.5^\circ\text{C}$  [ $\pm 1^\circ\text{F}$ ]

**3-year warranty**

