

sinopé



Non-Programmable Thermostat for Electric Heating TH1124NP



Electric baseboard



Fan-forced convector (long cycle)



Convector (short cycle)



Radiant ceiling heating

■ FEATURES

- Accuracy of $\pm 1^\circ\text{F}$ [$\pm 0.5^\circ\text{C}$] for maximum savings and comfort
- Silent TRIAC switching
- Elegant backlit display
- Simple installation [2 non-polarized wires]
- Temperature displayed in $^\circ\text{C}$ or $^\circ\text{F}$

Mounting screws and wire connectors included

■ CERTIFICATION



■ STANDARDS

Conforms to CSA-C828-19

■ TECHNICAL SPECIFICATIONS

Operating voltage: 120/208/240 Vac, 60 Hz
Bilateral triode switch (triac)

Maximum load (resistive load only):

16.7 A / 4000 W @ 240 Vac

16.7 A / 2000 W @ 120 Vac

Minimum load:

Baseboard, convector and radiant ceiling

2 A / 500 W @ 240 Vac

2 A / 250 W @ 120 Vac

Fan-forced convector

4.16 A / 1000 W @ 240 Vac

4.16 A / 500 W @ 120 Vac

Setpoint range: 41 $^\circ\text{F}$ to 86 $^\circ\text{F}$ [5 $^\circ\text{C}$ to 30 $^\circ\text{C}$]

Display range: 32 $^\circ\text{F}$ to 99 $^\circ\text{F}$ [0 $^\circ\text{C}$ to 50 $^\circ\text{C}$]

Storage: -4 $^\circ\text{F}$ to 122 $^\circ\text{F}$ [-20 $^\circ\text{C}$ to 50 $^\circ\text{C}$]

Operation: 32 $^\circ\text{F}$ to 122 $^\circ\text{F}$ [0 $^\circ\text{C}$ to 50 $^\circ\text{C}$]

Resolution: $\pm 1^\circ\text{F}$ [$\pm 0.5^\circ\text{C}$]

3-year warranty

