

sinopé



Smart Floor Heating Thermostat
TH1300ZB-C4



Heating cables



Heating cable mats

CONNECTS WITH
Control4®
CERTIFIED

■ FEATURES*

- Backlit display
- Detects the connected load
- Lockable buttons
- Allows floor or ambient temperature control
- Indoor and outdoor or setpoint temperatures displayed on the thermostat screen
- Possibility to know the status of the GFCI
- Personalization of the minimum and maximum temperatures available for thermostat control
- Temperature displayed in °C or °F

This thermostat is equipped with:

- Floor sensor output**
- Auxiliary heating control or expansion unit output
- Protection for engineered wood flooring
- Built-in ground fault circuit interrupter (Class A GFCI)

* These features are available in Neviweb and require the GT130 hub. Features may vary from a platform to another.

**Floor sensor (15 ft) included.

■ COMMUNICATION

Protocol: Zigbee 3.0
Frequency: 2.4 GHz
Transmission power: +20 dBm
Receiver sensitivity: -108 dBm
Encryption key: AES-128

■ ACCESSORIES



Expansion Unit TR1310

For any installation exceeding 15 A, use the expansion module in addition to the thermostat.



Floor Sensor AC1310-01

Complete your installation like a pro by adding a 2nd sensor during installation.

- Remote control with your smartphone, tablet or computer*
- Schedule programming
- Voice control with Amazon Alexa and Google Assistant

* Remote access requires a permanent Internet connection and a Control4 controller.

■ TECHNICAL SPECIFICATIONS

Operating voltage: 120/208/240 Vac, 50/60 Hz

Maximum load:

1800 W @ 120 V / 15 A

3120 W @ 208 V / 15 A

3600 W @ 240 V / 15 A

Setpoint range: 5 °C to 36 °C [41 °F to 97 °F]

Display range: 0 °C to 50 °C [32 °F to 99 °F]

Resolution: ± 0.5 °C [± 1 °F]

Storage: -20 °C to 50 °C [-4 °F to 122 °F]

Auxiliary output: 24 Vac / Vdc / 0.1 A

Compatibility: 10K Ω / 12K Ω sensors at 25 °C

Floor sensor included

3-year warranty

■ CERTIFICATION



■ STANDARDS

TB713-C Base: Conforms to ANSI/UL Std. 943

Certified under CAN/CSA Std. C22.2 No. 144.1

