



Ductless heat pump interface

HP6000ZB-MA





Ductless heat pumps and air conditioners equipped with a compatible communication port

*Possibility to combine the HP6000ZB-MA with the TH1134ZB/HC thermostat for a better use of the electric baseboard heater and the heat pump in the same room (air conditioning and heating interlocking).









FEATURES

- Allows to control the heat pump via the platforms [Neviweb and Sinopé Smart Systems]
- Possibility to ignore the remote control of the heat pump to control it only with Sinopé Smart Systems and/or Neviweb and/or with the Sinopé TH1134ZB/HC thermostat
- Associated with the TH1134ZB/HC thermostat, the HP6000ZB-MA allows the interlocking of the air conditioning and the electric heating in the same room
- *These features are available in Neviweb and Sinopé Smart Systems and require the use of the GTI30 gateway. The features may vary from one platform to another


COMMUNICATION

Protocol: Zigbee 3.0 Frequency: 2.4 GHz

Transmission power: +20 dBm Receiver sensitivity: -108 dBm Encryption key: AES-128

STANDARDS

Complies with FCC15 /NMB-003





- Control modes*: Cool, Heat, Dry, Fan and OFF
- · Adjustment of the orientation of the heat pump louvers
- · Adjustment of the fan intensity
- · Activation or deactivation of the display on the heat pump head
- Create automations that run based on time, sunrise/sunset, device action, or your presence
- Automate the interlocking of air conditioning and heating in all rooms of the house thanks to an automation between devices with the Sinopé thermostats of the different rooms.
- Activate personalized ambiances according to the time of the day, events or activity thanks to the scenes
- Setpoint control
- Voice assistants: Works with Amazon Alexa and Google Assistant
- Advanced features in Sinopé Smart Systems (e.g. prioritization of heating by the heat pump when it is more efficient than the baseboards)***

These features are available in Neviweb and Sinopé Smart Systems and require the use of the GTI30 gateway. The features may vary from one platform to another.

- * Feature available on models that allow this function
- **Requires the TH1134ZB/HC heating and cooling line thermostat

COMPATIBLES HEAT PUMPS



Scan the QR code to see which heat pumps and air conditioners are compatible with the HP6000ZB-MA.

■ TECHNICAL SPECIFICATIONS

Power supply: via heat pump / air conditioner communication port

Operating temperature: 32 °F to 104 °F [0 °C to 40 °C]

Storage: -4 °F to 122 °F (-20 °C to 50 °C)

3-year warranty



The HP6000ZB-MA interface can be combined with a TH1134ZB/HC thermostat for better use of the heating devices and ductless heat pump in the same room. Once the two units are combined, the TH1134ZB/HC ensures that the right heating system is running to maximize energy savings.

TH1134ZB-HC

sinopé

T: 450.741.7700 TF: 1.855.741.7701

sinopetech.com - sales@sinopetech.com Saint-Jean-sur-Richelieu, Qc, Canada