




## Smart Thermostat Pro for Central Heating TH6500WF

Compatible with most systems (one or more heating/cooling systems)



Electric



Geothermal



Fossil



Heat pump

More information:



## ■ FEATURES

- Touchscreen color display allowing personalized display (weather, time, indoor and outdoor temperatures, etc.)
- Multiple control modes available (heating, cooling, fan, etc.)
- Lights up when presence is detected by proximity sensor (if On Demand mode selected)
- Compatible with electricity supplier demand management programs
- Compatible with dual-energy
- Number of stages supported
  - Heat pump: supports up to 4 heating stages and 2 cooling stages
  - Classic: supports 2 heating stages and 2 cooling stages
- Automatic detection of installation configuration
- Bilingual interface
- Command output for air exchanger or humidifier start-up (according to customer's installation)
- Activate system fan in addition to air exchanger (HRV input)

## ■ COMMUNICATION


Protocol: Wi-Fi

Standard: IEEE 802.11 b/g/n

Frequency: 2.4 GHz

## ■ ACCESSORIES

**Decorative plate :** Add the decorative plate to your installation to make it more attractive



ineviweb



- **Schedule:** set a different schedule for each day of the week, up to 12 periods per day
- **Scenes:** activate personalized ambiances according to the time of the day, events, or activity
- **Energy reports:** monitor your consumption and savings in real-time
- **Geofencing:** trigger actions based on your presence
- **Voice assistants:** works with Amazon Alexa and Google Assistant
- **Éco Sinopé\*:** compatible with the Éco Sinopé feature, allowing you to reduce energy consumption during peak periods and save on your electricity bill
- **Alerts:** receive maintenance alerts (e.g. replace air filter)

\*Feature only available in Neviweb

## ■ TECHNICAL SPECIFICATIONS

Operating voltage: 24V AC

Maximum setpoint: 5 °C to 30 °C [41 °F to 86 °F]

Minimum setpoint: 10 °C to 40 °C [59 °F to 86 °F]

Storage: -20 °C to 50 °C [-4 °F to 122 °F]


Compatible with highly energy-efficient heat pumps operating down to -30°C

**Installation:** Only 2 wires required between thermostat and connection module

**Connection module included (TB6500):**

Connects directly to the heating system

**5-year warranty**



sinopé

T: 450.741.7700  
TF: 1.855.741.7701

sinopetech.com - sales@sinopetech.com  
Saint-Jean-sur-Richelieu, Qc, Canada

Neviweb is a trademark of Sinopé Technologies Inc., registered in Canada and the U.S.  
Amazon, Alexa and all related logos are trademarks of Amazon.com, Inc. or its affiliates.  
Google is a trademark of Google LLC.

Apple, Apple Watch, HomeKit, iPad, iPad Air, and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. HomePod is a trademark of Apple Inc.  
The Wi-Fi CERTIFIED™ Logo is a certification mark of Wi-Fi Alliance®