




Smart Thermostat Pro Lite for Central HVAC Systems

TH6250WF-PRO

Compatible with most single- and multi-stage HVAC systems



Electric



Geothermal



Fossil



Heat pump

More information:



sinopé



COMPATIBLE WITH
Amazon Alexa



sinopé



■ FEATURES

- Color touchscreen showing all key information (weather, time, indoor and outdoor temperatures, etc.)
- Multiple control modes available (heating, cooling, fan, etc.)
- Lights up when presence is detected by proximity sensor (if On Demand mode is selected)
- Compatible with utility demand-response programs
- Compatible with dualenergy
- Number of stages supported
 - Heat pump: supports up to 2 heating stages and 1 cooling stage
 - Conventional: supports 1 heating stage and 1 cooling stage
- Automatic detection of installation configuration
- Bilingual interface

■ COMMUNICATION

Protocol: Wi-Fi


Standard: IEEE 802.11 b/g/n

Frequency: 2.4 GHz

■ ACCESSORIES

Decorative plate (included): Enhances the appearance of your installation.

When a junction box is present, the decorative wall plate must be used to ensure proper and safe coverage.



sinopé



- **Schedule:** set a different schedule for each day of the week, up to 12 periods per day
- **Scenes:** create personalized scenes based on the time of day, events, or activities
- **Energy reports:** monitor your energy consumption and savings in real time
- **Geofencing*:** automatically trigger actions based on your presence
- **Voice assistants*:** works with Amazon Alexa and Google Assistant
- **Éco Sinopé*:** integrates with Éco Sinopé, helping reduce energy consumption during peak periods and lower electricity cost
- **Alerts:** receive maintenance reminders (e.g., replace the air filter)

*Feature only available in the Sinopé Neviweb app

■ CONNECTIONS

Connection	Description
C	Common for 24 Vac power supply
R	24 Vac power supply from the heat pump
G	Circulation fan
W	First stage of heating or first stage of auxiliary heating
O/B	Reversing valve control output
Y	First stage of the heat pump or air conditioner
ACC	Accessory connection for external equipment and accessories equipment
IN	Dual energy input

■ TECHNICAL SPECIFICATIONS

Operating voltage: 24 Vac

Heating setpoint range: 5 °C to 30 °C (41 °F to 86 °F)

Cooling setpoint range: 15 °C to 36 °C (59 °F to 97 °F)

Storage temperature: -20 °C to 50 °C [-4 °F to 122 °F]


Connectors: 8 connectors

• Wire range (Solid): 18-22 AWG

• Wire range (Stranded): 20-22 AWG

• Wire clearance manufacturer's recommendation: 6.5 - 7.0 mm

5-year warranty



sinopé

T: 450.741.7700
TF: 1.855.741.7701

sinopetech.com - sales@sinopetech.com
Saint-Jean-sur-Richelieu, Qc, Canada

Neviweb is a trademark of Sinopé Technologies Inc., registered in Canada and the U.S.

Google is a trademark of Google LLC.

Apple, Apple Watch, HomeKit, iPad, iPad Air, and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. HomePod is a trademark of Apple Inc.

The Wi-Fi CERTIFIED™ Logo is a certification mark of Wi-Fi Alliance®